


Filters and Strainers MONO-IN-LINE – ANSI150 BOLTED

Sizes :	1" to 12" Nominal Bore
Pressure:	ANSI Class 150 lbs
Flanges:	ASME B16.5 RF
Features:	 Integrally cast housing Bolted closure Red oxide finish (Carbon Steel only) Ø 3 mm perforated hole plate as standard Integral feet on 6" and over
Advantages:	 Largest filtration area on the market Very low pressure losses dp Extended cleaning intervals European design
Options:	 Special baskets and special gaskets DP tappings / gauge Magnetic basket insert Flanged drains Drain valves Special finish / linings
Standards:	PED 2014/68/EU ASME B16.5 Flange dimensions EN 10204 / NACE Certification



All data is subject to confirmation at the time of order. Our policy is one of continual improvement and we reserve the right to amend details without prior notice.

Si	ze		Dimensions						Baske Area	-	Vent (NPT)		Weight		
mm	Inch	Α	В	С	D		E	F	[cm²]		(INPT)	(NPT)	(kg)		
25	1"	225,0	265,0	28,0	190	,0 2	225,0	200,0	241,0		1⁄4"	3/4"	6,5		
40	11⁄2"	240,0	335,0	35,0	254	,0 2	297,0	275,0	375,0		1⁄4"	3⁄4"	11,0		
50	2"	315,0	395,0	38,0	314	,0 3	362,0	340,0	488,0		1⁄4"	3/4"	30,0		
80	3"	365,0	450,0	40,0	342	,0 4	111,0	375,0	652,0		³ ⁄8"	³ /4"	34,0		
100	4"	445,0	550,0	47,0	426	,0 5	505,0	450,0	1088,0		³ ⁄8"	1"	70,0		
150	6"	600,0	790,0	95,0	619	,0 7	734,0	630,0	2151,0		1⁄2"	1½"	135,0		
200	8"	715,0	1000,0	112,5	787	,0 9	927,0	800,0	3973,0		1⁄2"	1½"	235,0		
250	10"	855,0	1160,0	120,0	908	,0 10	0,77	940,0	5304,0		1⁄2"	11⁄2"	380,0		
300	12"	1015,0	1320,0	88,0	1000	,0 12	215,0	1180,0	8295,0		1⁄2"	2"	530,0		
				Materi	als o	of Co	onst	ructio	า	-			-		
lt	em		LT Carbon Steel				Carbon Steel				Stainless Steel				
	oody (cast) ASTM A352 LCB/LCC Dual Cert ASTM A216 WCB (~1.0						CB (~1.061								
Strainer of	cover*	ASTM A352 LCB/LCC Dual Cert ASTM A516 Gr60 / A216 W						CB ASTM A240 316 / A351 CF8M (~1.4408)							
Drain plu	g	ASTM A350 LF2 ASTM A105N (~1.0460)						ASTM A182 F316 (~1.4404)							
Vent plug		ASTM A350 LF2 ASTM A105N (~1.0460)						ASTM A182 F316 (~1.4404)							
Strainer b	basket	5	Stainless Steel 316 (Ø 3 mm perforated hole plate as standard / to customer specification)												
Cover ga	sket		C.N.A.F. as standard / to customer specification												
Cover stu	id bolts	ASTM A193 B7M – zinc plated													
Cover ful	Inuts	ASTM A194 2HM – zinc plated													
Cover wa	sher		Carbon steel – zinc plated												

*The strainer cover may be furnished from plate or casting depending upon size / availability.

:

Model Number Derivation

A*<u>*</u>*/R15/<u>*</u>*/MBC

Size, i.e. add 025 for a 1"

352 for Low Temperature Carbon Steel 216 for carbon steel (A216 WCB) 351 for stainless steel (A351 CF8M)