1/1

Sizes 1" to 12" Nominal Bore

Pressure: ANSI Class 300 lbs

Features: - Integrally cast housing

- Bolted closure

- Red oxide finish (Carbon Steel only) - Ø 3 mm perforated hole plate as standard

- Integral feet on 6" and over

Advantages: - Largest filtration area on the market

- Very low pressure losses dp - Extended cleaning intervals

- European design


Options: - Special baskets and special gaskets

- DP tappings / gauge - Magnetic basket insert - Flanged drains - Drain valves

- Special finish / linings

Standards: PED 2014/68/EU

ANSI B16.5 RF Flange dimensions EN 10204 / NACE Certification



All data is subject to confirmation at the time of order. Our policy is one of continual improvement and we reserve the right to amend details without prior notice.

Technical Data											
Size		Dimensions						Basket Area	Vent	Drain (NDT)	Weight
mm	Inch	Α	В	С	D	Е	F	[cm²]	(NPT)	(NPT)	(kg)
25	1"	232,0	265,0	25,0	190,0	225,0	200,0	241,0	1/4"	3/4"	7,0
40	11/2"	245,0	335,0	35,0	254,0	297,0	275,0	375,0	1/4"	3/4"	12,0
50	2"	321,0	400,0	38,0	314,0	362,0	340,0	488,0	1/4"	3/4"	31,0
80	3"	375,0	455,0	40,0	342,0	411,0	375,0	652,0	3/8"	3/4"	35,0
100	4"	455,0	555,0	47,0	426,0	508,0	450,0	1088,0	3/8"	1"	73,0
150	6"	620,0	800,0	95,0	619,0	749,0	630,0	2151,0	1/2"	11/2"	142,0
200	8"	740,0	1020,0	109,5	787,0	952,0	800,0	3973,0	1/2"	11/2"	242,0
250	10"	890,0	1180,0	120,0	908,0	1103,0	940,0	5304,0	1/2"	1½"	390,0
300	12"	1050,0	1350,0	175,0	1000,0	1215,0	1180,0	8295,0	1/2"	2"	540,0

Materials of Construction									
Item	LT Carbon Steel	Carbon Steel	Stainless Steel						
Strainer Body	ASTM A352 LCB/LCC Dual Cert	ASTM A216 WCB (~1.0619)	ASTM A351 CF8M (~1.4408)						
Strainer Cover*	ASTM A352 LCB/LCC Dual Cert	ASTM A516 Gr60 / A216 WCB	ASTM A240 316 / A351 CF8M (~1.4408)						
Drain Plug	ASTM A350 LF2	ASTM A105N (~1.0460)	ASTM A182 F316 (~1.4404)						
Vent Plug	ASTM A350 LF2	ASTM A105N (~1.0460)	ASTM A182 F316 (~1.4404)						
Cover Stud Bolts	ASTM A320 L7M – zinc plated	ASTM A193 B7M – zinc plated							
Cover Full Nuts	ASTM A194 Gr.7M – zinc plated	ASTM A194 2HM – zinc plated							
Cover Gasket (flat)	C.N.A.F. as standard / to customer specification								
Screen (perforated)	SS 316 (~1.4404) (Ø 3 mm perforated hole plate as standard / to customer specification)								

A***/R30/***/MBC

Model Number Derivation:

Denotes the size, i.e. add '025' for a 1"

352 for Low Temperature Carbon Steel 216 for Carbon Steel 351 for Stainless Steel

Mono-In-Line ANSI300 Bolted en 04.doc

^{*}The strainer cover may be furnished from plate or casting depending upon size/availability.