1/1



Sizes: DN15 to DN300

Pressure: PN40

Flanges: PN40 EN 1092-1

Features: - Integrally cast housing

- Bolted cover c/w drain plug

Red oxide finish (Carbon Steel only)Ø 3 mm perforated hole plate as standard

Advantages: - Largest filtration area on the market

Very low pressure lossesExtended cleaning intervals

- European design


Options: - Special screens and special gaskets

D.P. tapping/gaugeMagnetic screen insertFlanged drains / drain valves

- Special finish / linings

Standards: PED 2014/68/EU

CE-Marking (from DN32) EN 10204 / NACE Certification Design code ASME VIII, Div. 1



All data is subject to confirmation at the time of order. Our policy is one of continual improvement and we reserve the right to amend details without prior notice.

Technical Data								
Size		Dimensions				Screen Area	Weight	
mm	Inch	Α	В	С	D (NPT)	[cm²]	(kg)	
15	1/2"	175,0	95,0	165,0	1/2"	80,0	3,5	
20	3/4"	177,0	95,0	165,0	1/2"	80,0	4,5	
25	1"	195,0	110,0	185,0	1/2"	127,0	6,3	
40	11⁄2"	270,0	140,0	230,0	1/2"	199,0	13,0	
50	2"	310,0	180,0	285,0	1/2"	333,0	18,0	
80	3"	386,0	220,0	355,0	1/2"	574,5	34,5	
100	4"	475,0	260,0	410,0	1/2"	925,0	54,5	
150	6"	565,0	340,0	550,0	1/2"	1894,0	120,0	
200	8"	715,0	440,0	705,0	3/4"	2870,0	215,0	
250	10"	890,0	600,0	1000,0	3/4"	5005,0	420,0	
300	12"	1052,0	640,0	1040,0	3/4"	6375,0	695,0	

Materials of Construction								
Item	LT Carbon Steel	Carbon Steel	Stainless Steel					
Strainer Body	ASTM A352 LCB/LCC Dual Cert	ASTM A216 WCB (~1.0619)	ASTM A351 CF8M (~1.4408)					
Strainer Cover*	ASTM A352 LCB/LCC Dual Cert	ASTM A516 Gr60 / A216 WCB	ASTM A240 316 / A351 CF8M (~1.4408)					
Drain Plug (forged)	ASTM A350 LF2	ASTM A105N (~1.0460)	ASTM A182 F316 (~1.4404)					
Cover Stud Bolts	ASTM A320 L7M – zinc plated ASTM A193 B7M – zinc plated							
Cover Full Nuts	ASTM A194 Gr.7M – zinc plated ASTM A194 2HM – zinc plated							
Cover Gasket (flat)	C.N.A.F. as standard / Spiral wound SS316 & Graphite (optional) / to customer specification							
Screen (perforated) SS 316 (~1.4404) (Ø 3 mm perforated hole plate as standard / to customer specification)								

^{*}The strainer cover may be furnished from plate or casting depending upon size/availability.

Model Number Derivation:

Denotes the size, i.e. add '025' for a 1"

A***/**PN40**/***/**YMD**

352 for Low Temperature Carbon Steel 216 for Carbon Steel 351 for Stainless Steel